

SPECIFICATIONS



Model	Dimensions	Weight
XB3600	(36" Diameter x 29.3"H)	126 lbs
XB3636	(36"L x 36"W x 29.3"H)	139 lbs
XB4200	(42" Diameter x 29.3"H)	142 lbs
XB4242	(42"L x 42"W x 29.3"H)	162 lbs
XB4800	(48" Diameter x 29.3"H)	164 lbs

*Intended for indoor use only



DETAILS

Color

Base: Black Slate Laminate

Top: Kensington Maple, Asian Sun, Wild Cherry, Montana Walnut with coordinating edge. Titanium Evolve and Titanium Evolve Game Top with black edge.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

1¹/₄" thick laminate top with black vinyl T-mold edge

Assembly

Refer to manufacturer's instructions for assembly.

Fabrication & Material

Base: Two interlocking base panels. 1⁵/₈" thick 45 lb density particle board, sandwiched between 1¹/₈" thick hardboard and faced both sides with .050" thick, high-pressure laminate and banded on three exposed edges with heavy duty T-molding that is glued and steel pinned every twelve inches. An intermediate mounting plate joins the base to the top.

Top: Premium M3 Grade, 45 lb. density particle board table top core is sandwiched between 1¹/₈" thick hardboard and faced with special 0.05" thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel to steel connection for maximum long term reliability. Robust 1.5" thick edge profile.

Made in the U.S.A.

Installation

None required

Warranty

10 year limited replacement warranty

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

TESTING

Performance Test Standards

Product tested to 1,000 lb static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG